


Technical data sheet

Wiring trunking, type CABLIX 4060 S

Item number: 6132626



Wiring trunking, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Retainers are broken out without tools. Special lengths on request.
Tested to DIN EN 50085-2-3.
Base and cover in set.



PVC Polyvinylchloride

Master data

Item number	6132626
Type	CABLIX 4060 S
Description 1	Slotted cable trunking system
Description 2	CABLIX Set 40x60 7030
Manufacturer	OBO
Colour	Stone grey; RAL 7030
Material	Polyvinylchloride
Smallest sales unit	2
Unit of quantity	Metre
Weight	43.3 kg
Weight unit	kg/100 m


Technical data sheet

Wiring trunking, type CABLIX 4060 S

Item number: 6132626



Dimensions



Length	2,000 mm
Width	60 mm
Height	40 mm

Technical data

Side wall version	Slotted
Fastening type	Base perforation
Flexible	no
Halogen-free	no
Creepage current-resistant	yes
With cover	yes
Usable cross-section	19.5 cm ²
Slot spacing	6.5 mm
Slot width	6 mm
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C