


Technical data sheet

CABLIX 60 wiring ducts, duct width 60

Item number: 6132631



Wiring trunking, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Retainers are broken out without tools. Special lengths on request.
Tested to DIN EN 50085-2-3.
Base and cover in set.



PVC Polyvinylchloride

Master data

Item number	6132631
Type	CABLIX 6060 BL
Description 1	Slotted cable trunking system
Description 2	CABLIX Set 60x60
Manufacturer	OBO
Dimension	2000x60x60
Colour	Blue
Material	Polyvinylchloride
Smallest sales unit	2
Unit of quantity	Metre
Weight	53.3 kg
Weight unit	kg/100 m


Technical data sheet

CABLIX 60 wiring ducts, duct width 60

Item number: 6132631



Dimensions



Length	2,000 mm
Width	60 mm
Height	60 mm

Technical data

Side wall version	Slotted
Fastening type	Base perforation
Flexible	no
Halogen-free	no
Creepage current-resistant	yes
With cover	yes
Usable cross-section	30.35 cm ²
Slot spacing	6.5 mm
Slot width	6 mm
Self-extinguishing	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C