


Technical data sheet

Wiring trunking, type CABLIX 80120 S

Item number: 6132646



Wiring trunking, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Retainers are broken out without tools. Special lengths on request.
Tested to DIN EN 50085-2-3.
Base and cover in set.



PVC Polyvinylchloride

Master data

Item number	6132646
Type	CABLIX 80120 S
Description 1	Slotted cable trunking system
Description 2	CABLIX Set 80x120 7030
Manufacturer	OBO
Colour	Stone grey; RAL 7030
Material	Polyvinylchloride
Smallest sales unit	2
Unit of quantity	Metre
Weight	97 kg
Weight unit	kg/100 m


Technical data sheet

Wiring trunking, type CABLIX 80120 S

Item number: 6132646



Dimensions



Length	2,000 mm
Width	120 mm
Height	80 mm

Technical data

Side wall version	Slotted
Fastening type	Base perforation
Flexible	no
Halogen-free	no
Creepage current-resistant	yes
With cover	yes
Usable cross-section	86.8 cm ²
Slot spacing	6.5 mm
Slot width	6 mm
Self-extinguishing	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C