

Technical data sheet

Flat angle cover, for device installation trunking Rapid 80 type 70130

Item number: 6274423



Flat angle cover fitting made of halogen-free PC/ABS for simple creation of a rising or falling 90° change of direction with device installation trunking of the series Rapid 80 GK, GKH, GS and GA. The flat angle cover fitting can be used for symmetrical and asymmetrical trunking types.



Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

Item number	6274423
Type	GK-FH70130SW
Description 1	Flat angle
Description 2	hood fitting
Manufacturer	OBO
Dimension	70x130
Colour	Jet black; RAL 9005
Material	Polycarbonate/Acrylnitrile-butadiene-styrene
Smallest sales unit	1
Unit of quantity	Piece
Weight	12.461 kg
Weight unit	kg/100 pc.

Dimensions

Length	172.5 mm
Width	138 mm
Height	73 mm

Technical data sheet

Flat angle cover, for device installation trunking Rapid 80
type 70130

Item number: 6274423



Technical data

Number of covers	1
Version for	Hood fitting
for duct width	130 mm
for trunking height	70 mm
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Cover mounting type	Cross-over
Mounting perforation in base	no
Cover width	0 mm
Cover width 2	0 mm
Cover width 3	0 mm
Change of direction	Vertical, rising/falling
Protective film	yes
Symmetrical	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Angle range, max.	90 mm
Angle range, min.	90 mm