

Technical data sheet

External corner, for device installation trunking Rapid 45-2
type GK-53100
Item number: 6113045



Wall and ceiling trunking, halogen-free, consisting of base and cover for mounting directly on the wall.
During installation, ensure that only halogen-free accessories and fastening materials are used.



PC/ABS Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

Item number	6113045
Type	GKH-AS53100RW
Description 1	External corner
Description 2	rigid form
Manufacturer	OBO
Dimension	189x189x100
Colour	Pure white; RAL 9010
Material	Polycarbonate/Acrylnitrile-butadiene-styrene
Smallest sales unit	1
Unit of quantity	Piece
Weight	40.4 kg
Weight unit	kg/100 pc.

Technical data sheet

External corner, for device installation trunking Rapid 45-2
type GK-53100

Item number: 6113045



Technical data

Number of covers	1
for duct width	100 mm
for trunking height	53 mm
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Cover width 2	0 mm
Cover width 3	0 mm
Protection rating	IP40
Protection rating IK code	IK08
Symmetrical	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-15 °C