

# Technical data sheet

## Flat angle PRO AP17055

Item number: 6132882



Flat angle as a fitting for changing the direction of the PROFILA device installation on trunking.  
Solid fitting for attaching to the wall.



**ASA** Acrylnitrile-styrene-acrylester

### Master data

Item number	6132882
Type	PRO AP17055 blc
Description 1	Flat angle
Description 2	PROFILA 55x170 9010
Manufacturer	OBO
Colour	Pure white; RAL 9010
Material	Acrylnitrile-styrene-acrylester
Smallest sales unit	1
Unit of quantity	Piece
Weight	18 kg
Weight unit	kg/100 pc.

### Dimensions

Length	203 mm
Width	203 mm
Height	57 mm

### Technical data

Version for	Hood fitting
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Mounting perforation in base	no
Cover width	0 mm
Cover width 2	0 mm
Cover width 3	0 mm

# Technical data sheet

Flat angle PRO AP17055

Item number: 6132882



## Technical data

Change of direction	Vertical, rising/falling
Protection rating	IP40
Protective film	no
Protection rating IK code	IK07.
Symmetrical	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Angle range, max.	90 mm
Angle range, min.	85 mm