Technical data sheet

Cover, angle-adjustable bend A4

Item number: 6037580



Cover for angle-adjustable bend fitting for lockable and screw-on cable trays in indoor and outdoor areas, to protect cables against damage and soiling. Fastening with pre-mounted sash locks and through attachment of the section cover. Suitable for all side heights.



CER

Α4

Stainless steel

2E

Bright, treated

Master data

Item number 6037580 Type RBD W 500 A4 Description 1 Cover Description 2 for bend, adjustable Manufacturer OBO Dimension B500mm Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece		
Description 1 Cover Description 2 for bend, adjustable Manufacturer OBO Dimension B500mm Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Item number	6037580
Description 2 for bend, adjustable Manufacturer OBO Dimension B500mm Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Туре	RBD W 500 A4
Manufacturer OBO Dimension B500mm Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Description 1	Cover
Dimension B500mm Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Description 2	for bend, adjustable
Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Manufacturer	OBO
Surface Bright, treated Surface standard Smallest sales unit 1	Dimension	B500mm
Surface standard Smallest sales unit 1	Material	Stainless steel
Smallest sales unit 1	Surface	Bright, treated
	Surface standard	
Unit of quantity Piece	Smallest sales unit	1
	Unit of quantity	Piece
Weight 198 kg	Weight	198 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.


Technical data sheet

Cover, angle-adjustable bend A4





Dimensions



Width	500 mm
Plate thickness	1 mm

Technical data

Bend (angle)	Adjustable
Number of turn buckles	2 St.
Fastening type	Sash lock
Maintain electrical functions	no
Suitable for mesh cable tray	no
Suitable for cable ladder	no
Suitable for cable tray	yes
Change of direction	Horizontal
Rustproof steel, pickled	no
Hinged	no
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C