## Technical data sheet

45° bend 60 FT

**Item number: 6036132** 



45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



## CER

St

Steel



Hot-dip galvanised

#### Master data

6036132
RB 45 615 FT
45° bend
for cable tray, horizontal
OBO
60x150
Steel
Hot-dip galvanised
DIN EN ISO 1461
1
Piece
63.6 kg
kg/100 pc.

### **Technical data sheet**

#### 45° bend 60 FT

**Item number: 6036132** 



# 

Width	150 mm
Height	60 mm
Plate thickness	0.8 mm
Dimension B	150 mm

#### Technical data

Bend (angle)	45°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	yes
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	10 St.
Rail thickness	1.25 mm
	*