
Technical data sheet

45° bend 85 FT

Item number: 6036230



45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 85 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



CER

St

Steel



Hot-dip galvanised

Master data

6036230
RB 45 810 FT
45° bend
for cable tray, horizontal
OBO
85x100
Steel
Hot-dip galvanised
DIN EN ISO 1461
1
Piece
62.8 kg
kg/100 pc.

Technical data sheet

45° bend 85 FT

Item number: 6036230



Dimensions 892 96 179

Width	100 mm
Height	85 mm
Plate thickness	0.8 mm
Dimension B	100 mm

Technical data

Bend (angle)	45°
Connector version	Integrated connector
Type	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	14 St.
Rail thickness	1.25 mm