Technical data sheet 45° bend 85 FT

Item number: 6036238





45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 85 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.




Master data

Item number6036238TypeRB 45 850 FTDescription 145° bendDescription 2for cable tray, horizontalManufacturerOBODimension85x500MaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1Unit de curatificationDiscon		
Description 145° bendDescription 2for cable tray, horizontalManufacturerOBODimension85x500MaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1	Item number	6036238
Description 2for cable tray, horizontalManufacturerOBODimension85x500MaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1	Туре	RB 45 850 FT
ManufacturerOBODimension85x500MaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1	Description 1	45° bend
Dimension 85x500 Material Steel Surface Hot-dip galvanised Surface standard DIN EN ISO 1461 Smallest sales unit 1	Description 2	for cable tray, horizontal
Material Steel Surface Hot-dip galvanised Surface standard DIN EN ISO 1461 Smallest sales unit 1	Manufacturer	OBO
Surface Hot-dip galvanised Surface standard DIN EN ISO 1461 Smallest sales unit 1	Dimension	85x500
Surface standard DIN EN ISO 1461 Smallest sales unit 1	Material	Steel
Smallest sales unit 1	Surface	Hot-dip galvanised
	Surface standard	DIN EN ISO 1461
Unit of quantity	Smallest sales unit	1
	Unit of quantity	Piece
Weight 236 kg	Weight	236 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Item number: 6036238





Width	500 mm
Height	85 mm
Plate thickness	1 mm
Dimension B	500 mm

Technical data

Bend (angle)	45°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	1 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	20 St.
Rail thickness	1.25 mm