### Technical data sheet 90° bend 110 FS





90° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used in indoor areas. Fastening material must be ordered separately.



### CER

St

Steel

FS

Strip galvanized

#### Master data

6036808
RB 90 140 FS
90° bend
for cable tray, horizontal
OBO
110x400
Steel
Strip galvanized
DIN EN 10346
1
Piece
292.7 kg
kg/100 pc.

## Technical data sheet 90° bend 110 FS



**Item number: 6036808** 

# 

Width	400 mm
Height	110 mm
Plate thickness	1 mm
Dimension B	400 mm
Dimension R	50 mm

#### Technical data

Bend (angle)	90°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	1 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	22 St.
Rail thickness	1.25 mm