Technical data sheet

90° bend 85 FT

Item number: 6036722



90° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 85 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



CER

St

Steel



Hot-dip galvanised

Master data

| 6036722 |
|----------------------------|
| RB 90 860 FT |
| 90° bend |
| for cable tray, horizontal |
| OBO |
| 80x600 |
| Steel |
| Hot-dip galvanised |
| DIN EN ISO 1461 |
| 1 |
| Piece |
| 475.5 kg |
| kg/100 pc. |
| |

Technical data sheet

90° bend 85 FT

Item number: 6036722



Dimensions 500 596 725

| Width | 600 mm |
|-----------------|--------|
| Height | 85 mm |
| Plate thickness | 1 mm |
| Dimension B | 600 mm |
| Dimension R | 50 mm |

Technical data

| Bend (angle) | 90° |
|---|----------------------|
| Connector version | Integrated connector |
| Туре | Bend, rigid |
| Maintain electrical functions | no |
| Material thickness, floor plate | 1 mm |
| With cover | no |
| Mounting perforation in base | yes |
| NATO hole pattern | no |
| Change of direction | Horizontal |
| Rustproof steel, pickled | no |
| Side perforation | yes |
| Permitted temperature range, max. | 120 °C |
| Permitted temperature range, min. | -20 °C |
| Wide-span version | no |
| Type of connector, cable support system | screwed/clamped |
| Recommended quantity of bolts | 20 St. |
| Rail thickness | 1.25 mm |