
### **Technical data sheet**

### Bend, angle-adjustable, 60 A2

**Item number: 6037156** 





Angle-adjustable bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Adjustable angle 0–90°. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.

# CERK

A2

Stainless steel

2E

Bright, treated

### Master data

Item number 6037156 Type RB W 630 A2 Description 1 Adjustable bend Description 2 horizontal Manufacturer OBO Dimension 60x300 Material Stainless steel
Description 1 Adjustable bend Description 2 horizontal Manufacturer OBO Dimension 60x300
Description 2 horizontal  Manufacturer OBO  Dimension 60x300
Manufacturer OBO Dimension 60x300
Dimension 60x300
Material Stainless steel
Surface Bright, treated
Surface standard
Smallest sales unit 1
Unit of quantity Piece
Weight 147.1 kg
Weight unit kg/100 pc.

# **Technical data sheet**

## Bend, angle-adjustable, 60 A2

**Item number: 6037156** 



# Dimensions 829

Width	300 mm
Height	60 mm
Plate thickness	1.25 mm
Dimension B	300 mm
Dimension L	678 mm
Dimension R	50 mm

### Technical data

Bend (angle)	Adjustable
Connector version	Integrated connector
Туре	Adjustable bend_complete
Maintain electrical functions	no
Material thickness, floor plate	1.25 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	14 St.
Rail thickness	1.25 mm