
Technical data sheet Bend, angle-adjustable, 60 A4

Item number: 6037180



Angle-adjustable bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Adjustable angle 0–90°. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.







Master data


Item number6037180TypeRB W 650 A4Description 1Adjustable bendDescription 2horizontalManufacturerOBODimension60x500MaterialStainless steelSurfaceBright, treatedSurface standard1
Description 1Adjustable bendDescription 2horizontalManufacturerOBODimension60x500MaterialStainless steelSurfaceBright, treatedSurface standard
Description 2 horizontal Manufacturer OBO Dimension 60x500 Material Stainless steel Surface Bright, treated Surface standard
Manufacturer OBO Dimension 60x500 Material Stainless steel Surface Bright, treated Surface standard Heat Stainless
Dimension 60x500 Material Stainless steel Surface Bright, treated Surface standard Stainless steel
Material Stainless steel Surface Bright, treated Surface standard Surface
Surface Bright, treated Surface standard
Surface standard
Smallest sales unit 1
Unit of quantity Piece
Weight 306.9 kg
Weight unit kg/100 pc.

Technical data sheet

Bend, angle-adjustable, 60 A4

Item number: 6037180





Width	500 mm
Height	60 mm
Plate thickness	1.25 mm
Dimension B	500 mm
Dimension L	992 mm

Technical data

Bend (angle)	Adjustable
Connector version	Integrated connector
Туре	Adjustable bend_complete
Maintain electrical functions	no
Material thickness, floor plate	1.25 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	Screwed
Recommended quantity of bolts	16 St.
Rail thickness	1.25 mm