## **Technical data sheet**

Cover, cross-over 100 A2

**Item number: 7027860** 



Cover for cross-over fitting for lockable and screw-on cable trays in indoor and outdoor areas, to protect cables against damage and soiling. Fastening through attachment of the section cover. Suitable for all side heights.

The cover can be used with fittings of all side heights.



# CER

A2

Stainless steel

2B

Bright, treated

#### Master data

Item number 7027860  Type RKD 100 A2  Description 1 Cover  Description 2 for cross-over  Manufacturer OBO  Dimension B100mm  Material Stainless steel  Surface Bright, treated  Surface standard  Smallest sales unit 1  Unit of quantity Piece		
Description 1 Cover Description 2 for cross-over Manufacturer OBO Dimension B100mm Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Item number	7027860
Description 2 for cross-over  Manufacturer OBO  Dimension B100mm  Material Stainless steel  Surface Bright, treated  Surface standard  Smallest sales unit 1	Туре	RKD 100 A2
Manufacturer OBO Dimension B100mm Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Description 1	Cover
Dimension B100mm  Material Stainless steel  Surface Bright, treated  Surface standard  Smallest sales unit 1	Description 2	for cross-over
Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Manufacturer	OBO
Surface Bright, treated Surface standard Smallest sales unit 1	Dimension	B100mm
Surface standard Smallest sales unit 1	Material	Stainless steel
Smallest sales unit 1	Surface	Bright, treated
	Surface standard	
Unit of quantity Piece	Smallest sales unit	1
The or quantity	Unit of quantity	Piece
Weight 23 kg	Weight	23 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

## **Technical data sheet**

#### Cover, cross-over 100 A2

**Item number: 7027860** 



#### Dimensions 100 mm Width Plate thickness 0.75 mm Dimension B 100 mm 96

Technical data		
	Number of turn buckles	0 St.
	Fastening type	On top
	Suitable for cable ladder	no
	Suitable for cable tray	yes
	Rustproof steel, pickled	no
	Permitted temperature range	120 °C

Permitted temperature range,