

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 48 mm

Item number: 7400281



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable duct cover. With separating retainer in the duct base. The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



- St** Steel
- FS** Strip galvanized

Master data

Item number	7400281
Type	S3 25048-2
Description 1	Underfloor duct, 2-part
Description 2	3 compartments
Manufacturer	OBO
Dimension	2000x250x48
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	453.8 kg
Weight unit	kg/100 m

Dimensions

Length	2,000 mm
Width	250 mm
Height	48 mm
Dimension a	90 mm
Dimension b	70 mm
Dimension h	48 mm

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height
48 mm

Item number: 7400281



Technical data

Number of fixed partitions	2
Number of compartments	3 St.
Floor plate	yes
Application area	Screed-covered
Decouplable	no
Trunking width, min.	250 mm
Duct height, min.	48 mm
Usable cross-section	10892 mm ²
Removable cover	yes
Cross-section, draw a	3854 mm ²
Cross-section, draw b	3184 mm ²