

## ISO-klem op voetstuk




Schroefbaar op schroefdraad M6.

Type	Span- bereik D mm	Kleur	Verp. Stuk	Gewicht kg/100 st.	Bestelnr.
2960 11 M6 LGR	9-11	lichtgrijs	50	0,549	2130114
2960 12 M6 LGR	12-13	lichtgrijs	50	0,480	2130122
2960 15 M6 LGR	15-17	lichtgrijs	50	0,510	2130157
2960 18 M6 LGR	16,5-18	lichtgrijs	50	0,791	2130181
2960 22 M6 LGR	20,5-22	lichtgrijs	50	0,951	2130211
2960 25 M6 LGR	22,5-25	lichtgrijs	25	1,221	2130254
2960 28 M6 LGR	25,5-28	lichtgrijs	25	1,341	2130289
2960 35 M6 LGR	31,5-35	lichtgrijs	25	1,761	2130351
2960 40 M6 LGR	36,5-40	lichtgrijs	20	3,017	2130408
2960 43 M6 LGR	40,5-43	lichtgrijs	20	3,098	2130432
2960 47 M6 LGR	45,5-47	lichtgrijs	15	4,235	2130475
2960 54 M6 LGR	50,5-54	lichtgrijs	15	4,524	2130548

**PS** Polystyreen

### Afmetingen



Type	Span- bereik D mm	Afmeting A mm	Afmeting B mm	Afm. x mm	Afme- ting H mm	Afm. d mm	Schroef- draad
2960 11 M6 LGR	9-11	35	25	2,2	11,6	17	M6
2960 12 M6 LGR	12-13	35	25	1	10	17	M6
2960 15 M6 LGR	15-17	38	28	0	11,5	18	M6
2960 18 M6 LGR	16,5-18	46	34	2	12	20	M6
2960 22 M6 LGR	20,5-22	50	38	2	14	21	M6
2960 25 M6 LGR	22,5-25	55	43	3	16	23	M6
2960 28 M6 LGR	25,5-28	58	46	3	17,5	24	M6
2960 35 M6 LGR	31,5-35	66	54	4	18,5	28	M6
2960 40 M6 LGR	36,5-40	80	66	4	23	34	M6
2960 43 M6 LGR	40,5-43	80	66	3	21	34	M6
2960 47 M6 LGR	45,5-47	98	82	2	22,5	36	M6
2960 54 M6 LGR	50,5-54	98	82	4	20	36	M6