

Design and connection along the whole length

Hidden connection technology in the installation trunking

Hidden cable routing
for sophisticated design requirements

Flexible equipment with sockets and
data/multimedia connections

Screed-flush mounting
of the trunking and continuous
floor covering

Building Connections

OBO
BETTERMANN

Seamless supply

A room completely without sockets, neither on the wall, nor on the floor. And still supplied with power and data? The OKB trunking system makes it possible. As the trunking is mounted flush with the screed and the covers are covered directly by the floor covering, they fit discreetly and seamlessly into any interior.



First mounting steps

- Mounted on the raw concrete before the screed work
- With inner and outer corners, the trunking can be adapted to the appropriate shape of the room



Ideal integration

- The screed side of the trunking possesses a support plate for the screed
- Screed contact edge serves as a drip edge and it allows screed-flush installation



The right level

- The system can be adjusted exactly to the planned screed height using the height-adjustment feet
- The floor structure from the top edge of the raw floor to the top edge of the finished screed must be at least 85 mm and a max. of 333 mm



Last installation steps

- Suitable for floor coverings such as parquet and plastic coverings up to a thickness of 25 mm
- Installation possible with sockets of the Modul 45connect series

OBO Bettermann Holding GmbH & Co. KG
P.O. Box 1120
58694 Menden
GERMANY

Customer Service Germany
Tel.: +49 (0)2373 89-1700
Fax: +49 (0)2373 89-1238
export@obo.de

www.obo-bettermann.com

OBO
BETTERMANN